

校温环外径与温度对照表 (TEMPERATURE TABLE FOR RTC)

产品型号(Type):				AQS 15		试验条件(Condition):				空气气氛下保温 1 小时	
适用温度范围(Temperature):				650 ℃ ~ 1000 ℃		允许误差范围(Deviation):				± 1 ℃ ~ 3 ℃	
校温环外径 Φ (mm)	烧成温度 T (℃)	校温环外径 Φ (mm)	烧成温度 T (℃)	校温环外径 Φ (mm)	烧成温度 T (℃)	校温环外径 Φ (mm)	烧成温度 T (℃)	校温环外径 Φ (mm)	烧成温度 T (℃)	校温环外径 Φ (mm)	烧成温度 T (℃)
		19.00	734	18.50	823	18.00	879	17.50	926		
		18.99	737	18.49	825	17.99	880	17.49	927		
		18.98	740	18.48	826	17.98	881	17.48	928		
		18.97	742	18.47	827	17.97	882	17.47	929		
		18.96	744	18.46	828	17.96	883	17.46	930		
19.45	650	18.95	746	18.45	829	17.95	884	17.45	931		
19.44	653	18.94	748	18.44	831	17.94	885	17.44	932		
19.43	656	18.93	751	18.43	832	17.93	886	17.43	933		
19.42	658	18.92	753	18.42	833	17.92	887	17.42	935		
19.41	660	18.91	755	18.41	834	17.91	888	17.41	936		
19.40	662	18.90	757	18.40	835	17.90	889	17.40	937		
19.39	664	18.89	759	18.39	837	17.89	889	17.39	938		
19.38	666	18.88	761	18.38	838	17.88	890	17.38	939		
19.37	667	18.87	764	18.37	840	17.87	891	17.37	940		
19.36	669	18.86	766	18.36	841	17.86	892	17.36	942		
19.35	670	18.85	768	18.35	842	17.85	893	17.35	943		
19.34	671	18.84	769	18.34	843	17.84	894	17.34	944		
19.33	673	18.83	771	18.33	844	17.83	894	17.33	946		
19.32	674	18.82	773	18.32	845	17.82	895	17.32	948		
19.31	676	18.81	775	18.31	846	17.81	896	17.31	950		
19.30	678	18.80	777	18.30	847	17.80	897	17.30	951		
19.29	679	18.79	779	18.29	848	17.79	898	17.29	953		
19.28	680	18.78	780	18.28	850	17.78	899	17.28	955		
19.27	682	18.77	782	18.27	851	17.77	900	17.27	957		
19.26	683	18.76	784	18.26	852	17.76	901	17.26	960		
19.25	685	18.75	786	18.25	853	17.75	902	17.25	963		
19.24	686	18.74	788	18.24	854	17.74	903	17.24	966		
19.23	688	18.73	789	18.23	855	17.73	904	17.23	970		
19.22	690	18.72	791	18.22	856	17.72	905	17.22	974		
19.21	691	18.71	792	18.21	857	17.71	905	17.21	978		
19.20	693	18.70	794	18.20	858	17.70	906	17.20	982		
19.19	694	18.69	795	18.19	859	17.69	907	17.19	986		
19.18	696	18.68	796	18.18	860	17.68	908	17.18	989		
19.17	698	18.67	798	18.17	862	17.67	909	17.17	991		
19.16	700	18.66	800	18.16	863	17.66	910	17.16	993		
19.15	702	18.65	802	18.15	864	17.65	911	17.15	994		
19.14	704	18.64	803	18.14	865	17.64	912	17.14	995		
19.13	706	18.63	804	18.13	866	17.63	913	17.13	997		
19.12	707	18.62	806	18.12	867	17.62	914	17.12	998		
19.11	709	18.61	807	18.11	868	17.61	915	17.11	999		
19.10	711	18.60	809	18.10	869	17.60	916	17.10	1000		
19.09	713	18.59	810	18.09	870	17.59	917				
19.08	716	18.58	811	18.08	871	17.58	918				
19.07	718	18.57	813	18.07	872	17.57	918				
19.06	720	18.56	815	18.06	873	17.56	919				
19.05	723	18.55	816	18.05	874	17.55	920				
19.04	725	18.54	817	18.04	875	17.54	921				
19.03	728	18.53	819	18.03	876	17.53	923				
19.02	730	18.52	820	18.02	877	17.52	924				
19.01	732	18.51	821	18.01	878	17.51	925				
产品规格:				Φ _{0.20} × Φ _{1.10} × h 7mm,		绿色 (Green)		检验工程师 (Inspector): 黄 满 连			
生产批号 (Batch No.):				AQS 15		生产日期 (Date): 2010-08-18					

ISO 9001:2000

